

# United States Resin Company

2625 Redwing Road, Suite 226  
Fort Collins, CO 80526

## Exchange Service Softener SS-Model

### General Description

The SS-Model Softener is compact and portable. It is a down-flow design with no moving parts. The tank is constructed of T-304 stainless steel of low carbon content with heli-arc welded top and bottom and fusion seam-welded shell. The top has three openings: one 1 1/2" threaded hole for filling the tanks and two 1" threaded holes in the top of the inlet and outlet tank connectors.

The complete SS-Model assembly includes: two 1" tank connectors; two plastic distributors\* - one short (inlet), on long (outlet); with outlet distributor seal rings; two distributor springs; two 1" plugs with "O" rings; one 1 1/2" plug with "O" ring; two 3/4" yoke assemblies with "O" rings.

\*Stainless Steel distributors (short and long) are available for hot water applications.

### Features

- 3/4" or 1" Full flow tank connectors
- Heavy-duty construction
- Stainless steel construction
- "O" ring seals
- High flow rate
- Compact
- Quick disconnect fittings
- Bar on side for easy handling



# United States Resin Company

2625 Redwing Road, Suite 226

Fort Collins, CO 80526

## Technical Data

Specifications	Expressed As	8"	10"
Rated Capacity (packaged bed)	Grains	41,000	61,000
Resin – Maximum Volume (packaged bed)	Cu. Ft.	1.14	1.72
Tank Shell	Gauge	14 (.072)	14 (.072)
Top and Bottom	Gauge	12 (.105)	12 (.105)
Tank Shell Diameter	Inches	8 1/8	10 1/4
Flow Rate – at 30 P.S.I. pressure drop at 15 P.S.I. pressure drop	G.P.M. G.P.M.	14.7 9.4	17.8 11.4
Pipe Size – Inlet and Outlet	Inches	3/4	3/4
Height, Overall (including Tank Connectors)	Inches	40 1/2	40 1/2
Weight, Full (approximately)	Pounds	98	133
Weight, Shell Only	Pounds	23	32
Bottom of Tank to Center of Tank Connector Opening	Inches	39 1/4 ± 1/16	39 1/4 ± 1/16

1. Threaded stainless steel fill opening.
2. Outward-domed top and bottom for maximum strength, minimum distortion, and capacity.
3. Heli-arc weld top, bottom, and fittings.
4. 3/4" or 1" flow tank connect yoke assemblies or quick-connect bypass valve.
5. These tanks have been hydrostatically tested at approximately 3 times standard household pressure.